

# IC-100

## CD Ignition System

### Description

The IC-100 is a microprocessor-controlled, spark capacitive discharge ignition system capable of supplying ignition energy for a wide range of gas engines with 1 to 8 cylinders.

The number of cylinders and the corresponding firing pattern, as well as the trigger disc configuration, are programmed individually.

Integral to the IC-100 is the capability for three-dimensional timing mapping:

- Potentiometer Curve (up to 38° Programmable Span)
- 0–5 V Analog Signal
- Cylinder/Cylinder Timing Adjustment

The IC-100 is capable of firing up to 8 cylinders with either one or two spark plugs per cylinder. In case of two spark plugs per cylinder, the corresponding ignition coils must be wired in series.

One pick-up senses impulses from a trigger disk mounted on the camshaft (single-firing) or crankshaft (double-firing). This information is sent to a microprocessor which controls the ignition system.

### Operational Features

The IC-100 has several functional features to ensure proper operation:

- Trigger Signal Check
- Input Signal Fault Recognition
- Shutdown
- Manual Ignition Energy Adjustment
- Hour Meter

#### Safety Features:

- Overspeed Shutdown
- Permissive Start Output
- Pick-up Fault Detection
- Internal Error Check
- Errors are Displayed via LED Flash Codes

#### Permissive Start:

A solid-state output is available capable of sinking 150 mA. This output can be used to power an external relay which could (for example) open the fuel valve.


**Technical Manual** 26205



- User programmable
- RS-232 and CAN communications
- Manually programmable energy allows adaptability to varying gas quality
- High energy system
- Programmable overspeed protection
- Adjustable energy levels could improve spark plug life
- CE Compliant

## Specifications

Power Consumption	24 V operation: 18–32 Vdc (2.2 A max.)
Trigger Input	Variable reluctance (passive) +2 Vdc min., 80 V p-p max, 10 Hz to 10 kHz
Sensor Inputs	0–5 V sensors
Permissive Start (solid-state output)	Open collector (NPN) 60 V max., 150 mA max
Communications Ports	CAN, RS-232
Ambient Operating Temperature	–40 to +55 °C (–40 to +131 °F)
Storage Temperature	–40 to +85 °C (–40 to +185 °F)
Mechanical Vibration	SV2: 4g, 5–2000 Hz and RV1: 8.2 Grms, 10–2000 Hz
Mechanical Shock	MS1: 40g peak, 11 ms sawtooth
Air Quality	Pollution Degree II
Installation Overvoltage	Category II



**IC-100 Ignition System (Do not use for construction)**



PO Box 1519, Fort Collins CO, USA 80522-1519  
 1000 East Drake Road, Fort Collins CO 80525  
 Tel.: +1 (970) 482-5811 ♦ Fax: +1 (970) 498-3058  
[www.woodward.com](http://www.woodward.com)

### Distributors & Service

Woodward has an international network of distributors and service facilities. For your nearest representative, call the Fort Collins plant or see the Worldwide Directory on our website.

This document is distributed for informational purposes only. It is not to be construed as creating or becoming part of any Woodward contractual or warranty obligation unless expressly stated in a written sales contract.

Copyright © Woodward 2000–2003, All Rights Reserved

For more information contact: